

# Juralco® Homestead Balustrade System

## BPIR Declaration

Version: 3-22 v1

---

### Designated building product: Class 2

---

### Declaration

HomePlus Wellington 2018 Limited trading as HomePlus Wellington has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

---

### Product/system

<b>Name</b>	Juralco® Homestead Balustrade System
<b>Line</b>	
<b>Identifier</b>	

---

### Description

The Juralco Homestead Balustrade System combines a contemporary Aluminium frame with an adjustable racking angle for stairs. The system is extremely versatile and can be installed in a range of configurations with powder-coat colours to meet most modern architectural requirements. Your compliance evidence.

---

### Scope of use

Homestead Balustrade System

- Domestic and Residential Occupancy types A, A Other and C3 only
- Is not suitable for Commercial C3 applications.

---

## Conditions of use

- Only extrusions, components and hardware supplied by or specified by JABP may be used in the Juralco Homestead System.
- Aluminium extrusions, components, and hardware – unless specified are manufactured to 6060 T5 specifications.
- Stainless Steel components, hardware, fixings – all components to 316 grade.
- The Juralco Homestead Balustrade System must only be installed in accordance with the Juralco Homestead Balustrade System manual.
- Any deviation from that specified in the Juralco Homestead Balustrade manual must only be in accordance with the site-specific PS1 and with site-specific calculations and drawings listing the nonstandard details.
- The Juralco Homestead Balustrade System must only be fabricated/installed by a Juralco approved fabricator • Upon completion of the installation the fabricator must supply the owner with a PS3 (Construction).

---

## Relevant building code clauses

**B1 Structure** — B1.3.1, B1.3.2, B1.3.3 (f, h, j), B1.3.4

**B2 Durability** — B2.3.1 (a), B2.3.2 (a, b)

**D1 Access Routes** — D1.3.3 (j, k)

**F2 Hazardous building materials** — F2.3.1

**F4 Safety from falling** — F4.3.1

---

## Contributions to compliance

- NZBC Compliance
- The Juralco Homestead Balustrade System has been reviewed by Lautrec Technology Group Ltd to demonstrate compliance with the structural requirements of the New Zealand Building Code and AS/NZS 1170: 2002 occupancy A, A Other and C3, NZS 3604 Low, Medium, High, Very High and Extra High Wind Zones max design wind pressure 2.5Kpa
- The Structural Engineering design includes the requirements of B1 Structure, B2 Durability and F4 Safety from falling, all from the Building Code.
- Verification Method B1 / VM1, B2/AS1, F4 / AS1
- Complies With AS/NZS 1170:2002, NZ Building Code Clauses B1, B2, and F4

---

## Supporting documentation

The following additional documentation supports the above statements:

<b>BA Homestead Balustrade</b>	3-22 v1	<a href="https://www.homeplus.co.nz/assets/Uploads/resources/BA-Homestead-Balustrade-3-22-v3.pdf">https://www.homeplus.co.nz/assets/Uploads/resources/BA-Homestead-Balustrade-3-22-v3.pdf</a>
<b>Producer Statement Request</b>	3-22 v1	<a href="https://ps1.homeplus.co.nz/">https://ps1.homeplus.co.nz/</a>
<b>HomePlus Warranty</b>	3-22 v1	<a href="https://www.homeplus.co.nz/warranty/">https://www.homeplus.co.nz/warranty/</a>
<b>Balustrade Care and Maintenance</b>	3-22 v1	<a href="https://www.homeplus.co.nz/warranty/care-and-maintenance/balustrade-care-and-maintenance/">https://www.homeplus.co.nz/warranty/care-and-maintenance/balustrade-care-and-maintenance/</a>

For further information supporting Juralco® Homestead Balustrade System claims refer to our website.

---

## Contact details

<b>Manufacture location</b>	New Zealand
<b>Legal and trading name of manufacturer</b>	HomePlus Wellington 2018 Limited trading as HomePlus Wellington
<b>Manufacturer address for service</b>	60A Victoria Street, Alicetown, Lower Hutt 5010
<b>Manufacturer website</b>	<a href="https://www.homeplus.co.nz/find-us/wellington/">https://www.homeplus.co.nz/find-us/wellington/</a>
<b>Manufacturer email</b>	wellington@homeplus.co.nz
<b>Manufacturer phone number</b>	04 589 0051
<b>Manufacturer NZBN</b>	9429046910790

---

## Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.

I can also confirm that Juralco® Homestead Balustrade System is not subject to a warning or ban under [s26 of the Building Act](#).

Signed for and on behalf of **HomePlus Wellington 2018 Limited trading as HomePlus Wellington:**

*Andrew Rodger*

Andrew Rodger  
DIRECTOR/OWNER  
December 2023

---

**HOMEPLUS WELLINGTON 2018 LIMITED TRADING AS HOMEPLUS WELLINGTON**  
60A Victoria Street, Alicetown Lower Hutt, 5010 New Zealand  
04 589 0051 | <https://www.homeplus.co.nz/find-us/wellington/>

# Appendix

---

## BPIR Ready selections

**Category:** Balustrades systems

	Yes	No
Use as pool fencing		x
Provides an accessible handrail	x	
Use of glass or other brittle material		x

---

## Building code performance clauses

### B1 Structure

#### B1.3.1

*Buildings, building elements and sitework* shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction* or *alteration* and throughout their lives.

#### B1.3.2

*Buildings, building elements and sitework* shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

#### B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings, building elements and sitework*, including:

- (f) earthquake
- (h) wind
- (j) impact

#### B1.3.4

Due allowances shall be made for:

- a. the consequences of failure,
- b. the intended use of the *building*,
- c. effects of uncertainties resulting from *construction* activities, or the sequence in which *construction* activities occur,
- d. variation in the properties of materials and the characteristics of the site, and
- e. accuracy limitations inherent in the methods used to predict the stability of *buildings*.

## B2 Durability

#### B2.3.1

*Building elements* must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- (a) the life of the building, being not less than 50 years, if: those building elements (including floors, walls, and fixings) provide structural stability to the building, or those building elements are difficult to access or replace, or failure of those building elements to comply with the building code would go undetected during both normal use and maintenance of the building

#### B2.3.2

Individual *building elements* which are components of a *building system* and are difficult to access or replace must either:

- (a) all have the same durability
- (b) be installed in a manner that permits the replacement of building elements of lesser durability without removing building elements that have greater durability and are not specifically designed for removal and replacement

## D1 Access Routes

#### D1.3.3

Access routes shall:

- (j) have smooth, reachable, and graspable handrails to provide support and to assist with movement along a stair or barrier
- (k) have handrails of adequate strength and rigidity as required by Clause B1 Structure

## F2 Hazardous building materials

#### F2.3.1

The quantities of gas, liquid, radiation, or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

## **F4 Safety from falling**

### F4.3.1

Where people could fall 1 metre or more from an opening in the external envelope or floor of a *building*, or from a sudden change of level within or associated with a *building*, a barrier shall be provided.