Juralco® Glaslide® Frameless Glass Sliding Panel System

BPIR Declaration

Version: 11-22 v1

Designated building product: Class 2

Declaration

J.A.K.E 2020 Limited trading as HomePlus Whakatane has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

| Name | Juralco® Glaslide® Frameless Glass Sliding Panel System |
|------------|---|
| Line | |
| Identifier | |

Description

The Juralco Glaslide Frameless Glass Sliding Panel System is fitted with 10,12 or 15mm Toughened Glass and is available in 2,3,4 or 6-door configurations running on multiple tracks. A Magnetic latching system automatically locks all the doors in the closed position in a single movement. Glass panels max 1.1m wide and 3.0m high depending on Wind Zone, Panel height and Glass thickness. The system is especially suitable for high-end Residential, to provide a Sliding Panel Wind Protection System.

Scope of use

The installation manual details the documents the Juralco Glaslide Frameless Glass Sliding Panel System refers to, in relation to the New Zealand Building Code, the manufacturer's documents, products used in the System and requirements in relation to fixing and surface finishing.

Glaslide Frameless Glass Sliding Panels are a permanent outdoor living system providing weather protection in a range of outdoor areas including patios, decks, extended courtyards, pool areas, cafe and bar courtyards, outdoor shopping areas etc.

Glaslide® glass doors ideal for windy locations (conform with NZS 4223.3.2016) Glass doors in 10mm, 12mm or 15mm thicknesses — maximum width and height determined by locations wind pressure.

Conditions of use

- Only extrusions, components and hardware supplied by or specified by JABP may be used in the Juralco Glaslide® Frameless Glass Sliding Panel System.
- Aluminium extrusions, components, and hardware unless specified are manufactured to 6060 T5 specifications.
- Stainless Steel components, hardware, fixings all components to 316 grade.
- The Juralco Glaslide® Frameless Glass Sliding Panel System must only be installed in accordance with the Juralco Glaslide Frameless Glass Sliding Panel System manual.
- Any deviation from that specified in the Juralco Glaslide® Frameless Glass Sliding Panel System manual must only be in accordance with the site-specific PS1 with site-specific calculations and drawings listing the non-standard details.
- The Juralco Glaslide® Frameless Glass Sliding Panel System must only be fabricated/installed by a Juralco approved fabricator.
- Upon completion of the installation the fabricator must supply the owner with a PS3 (Construction).

Relevant building code clauses

B1 Structure F2 Hazardous material

B1/VM1; AS/NZS 1170:2021; AS/NZS 1664.1:1997; NZS AS 1720.1.2022; NZS

3101:2006; NZS 3404:1997; NZS 4223.3:2016; NZS 4223.4:2008

Contributions to compliance

NZBC Compliance

The Juralco Glaslide® Frameless Glass Sliding Panel System has been reviewed by Lautrec Technology Group Ltd to demonstrate compliance with the structural requirements of the New Zealand Building Code, B1 Structure, B2 Durability (15 yrs.), F2 Hazardous material and in particular:

- AS/NZS 1170.0-2002 Structural Design Actions-Part 0: General Principals.
- AS/NZS 1170.1-2002 Structural Design Actions-Part 1: Permanent, imposed, and other actions.
- AS/NZS 1170.2-2021 Structural Design Actions-Part 2: Wind Actions.
- AS/NZS 1664.1:1997 Aluminium structures limit state design.
- NZS 3404:1997 Steel structures standard.
- NZS 1720.1:2022 Timber structures Part 1, Design Methods.
- NZS 4223.3:2016 Glazing in buildings Human impact and safety requirements.
- NZS 4223.4:2008 Glazing in buildings Wind, Dead, Snow and Live Actions.

Note: The Juralco Glaslide Frameless Glass Sliding Panel System is NOT a barrier for Safeguard from Falling (F4),

Glass Manifestation.

To be in accordance with NZS4223:3:2016

Note: NZS4223:3:2016 2.2.3 Housing: Manifestation is not required in Housing (See NZS4223:3:2016 section 3.1 for Building Type classifications). NZS4223:3:2016 2.2.4 Other Buildings: For other buildings, manifestation is required.

Supporting documentation

The following additional documentation supports the above statements:

| DW Glaslide® Frameless Glass Sliding Panels | 11-22 v1 | https://www.homeplus.co.nz/assets/Uploads/resources/DW-Glaslide-Frameless-Glass-Sliding-Panels-11-22-v1.pdf |
|---|------------------------|---|
| Producer Statement Request | 11-22 v1 | https://ps1.homeplus.co.nz/ |
| HomePlus Warranty | 11 December 2023 | https://www.homeplus.co.nz/warranty/ |
| Glaslide Care and Maintenance | 11 December 2023 | https://www.homeplus.co.nz/warranty/care- and-maintenance/glaslide-care-and- maintenance/ |

For further information supporting Juralco® Glaslide® Frameless Glass Sliding Panel System claims refer to our website.

Contact details

| Manufacture location | New Zealand |
|--|---|
| Legal and trading name of manufacturer | J.A.K.E 2020 Limited trading as HomePlus Whakatane |
| Manufacturer address for service | 34 Gateway Drive Whakatane 3120 |
| Manufacturer website | https://www.homeplus.co.nz/find-us/whakatane/ |
| Manufacturer email | whakatane@homeplus.co.nz |
| Manufacturer phone number | 07 307 0075 |
| Manufacturer NZBN | 9429048782968 |

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Juralco® Glaslide® Frameless Glass Sliding Panel System is not subject to a warning on ban under s26 of the Building Act.

Signed for and on behalf of J.A.K.E 2020 Limited trading as HomePlus Whakatane:

Evan Stewart

Evan Stewart
DIRECTOR/OWNER
December 2023

J.A.K.E 2020 LIMITED TRADING AS HOMEPLUS WHAKATANE 34 Gateway Drive, Whakatane 3120 New Zealand 07 307 0075 | https://www.homeplus.co.nz/find-us/whakatane/

Appendix

BPIR Ready selections

Category: Other (custom)